

INDOSIT™ CC 9022

(Wax Based Concrete Curing Compound)

INDOSIT™CC 9022 is a paraffin emulsion based, liquid concrete curing compound that prevents quick loss of water from the concrete with applied on fresh concrete surface.

Fields of Application:

- > Concrete roads and bridges,
- > Canal and canalette,
- > Airport and field concrete,
- > Concrete applications where there is plenty of air flow and evaporation and where there is less moisture.

Features & Benefits:

- > Resultant film retains sufficient moisture in the concrete to ensure full hydration of the cement
- > More effective than exhausting curing methods such as sack or canvas laying or water wetting.
- > Makes harder and dust-free surface.
- > Prevents shrinkage cracks resulting from fast drying while concrete surface is cured.
- > Water based, safely used in closed environments.

Technical Data:

Content	: Paraffin Emulsion
Color	: White
Density	: 0.97 kg/L
Flash Point	: None
Application Temperature	: > 5°C
Heat Resistance	: +5°C to +40°C

Application Method

INDOSIT™CC 9022 is applied with using spray gun or roller on fresh concrete. It is applied on primed field, road and slab concrete surfaces and on molded concrete surfaces which loss their glosses after strike.

Consumption:

3-4 m² per litre.

Cleanup Information:

Clean tools and equipment with industrial type solvents immediately after use. Dried material can only be removed mechanically.

Limitations

Foam may be observed in thick application. In this conditions, waiting for a while for disappearing foam, then scoured the surface again. In non-homogenous applications, regional color differences can be seen. It may be harmful with skin contact. Do not apply in freezing conditions or during precipitation. Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry. Do not use when air and surface temperatures are below +5°C and above +40°C. Avoid heavy traffic for 24 hours.

Warning

Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Shelf life:

12 months in original, unopened package.

Storage:

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Pack Size:

20 ,50 & 200 ltr plastic drum

Disclaimer:

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Manufacturer

Velosit India Pvt Ltd
209 Exim Link
Mulund Goregoan Link Road
Nahur West
Mumbai 400078

